4MT5
(CYJV CABLE ASSEMBLY)**Electrical connection**

Cable	PVC Yellow, 5.00 m
Cable diameter D	10.24 mm $\pm$ 0.20 mm
Conductor cross-section	16 AWG
Connection	7/8"-Male, straight, 3-pin
Connector configuration	Straight
Number of conductors	3
Number of pins	3
System	Molded

Electrical data

Cable rated voltage AC max.	600 V
Cable rated voltage DC max.	600 V
Operating voltage U_b	300 VDC / 300 VAC
Rated current (40 °C)	13.0 A

Environmental conditions

Cable temperature, fixed routing	-40...105 °C
IP rating	IP67, IP68

Remarks

Bulk cable: PVC UL listing, 16/3 STOOW/MaleOOW CSA FT2 105°C 600 V
 Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

General data

Approval/Conformity	cULus EAC WEEE
---------------------	----------------------


Material

Cable jacket, material	PVC
Material contact carrier	PUR
Material contacts	Brass
Material cover nut	Die-cast zinc
Material grip	PUR

Mechanical data

Cable jacket, color	yellow
Cable length L	5.00 m
Tightening torque pigtail	1.5 Nm

Connector Drawings



PIN 1: green
PIN 2: black
PIN 3: white

Wiring Diagrams

1 _____

2 _____

3 _____