

Catalog Number: UPC Number: Status:

Weight Uom

AF301B2-GV7A 80432579022 Active

Combination Starter, Non-Reversing, AF30, Three Phase, NEMA/UL Type 1, 3R, 4, 12 Enclosure, Control Voltage Rating 24VAC, Line Voltage 460-480V, Overload Relay Setting 24-29, Amp Rating 50A, with Start/Stop Pushbuttons

| North American Specifications (UNSPSC) | |
|--|--|
| UNSPSC | 39121521 Motor starter controls |
| IGCC | 4735 Non-Reversing Starters With Circuit Breaker |
| | Disconnects |
| Brand Name | ABB |
| Туре | Combination Starter |
| Special Features | Durable Protective Finish |
| Voltage Rating | 24VAC |
| Phase | Three |
| Size | AF30 |
| Enclosure | NEMA/UL Type 1, 3R, 4, 12 |
| Packaging | |
| Outer Quantity | 1 |
| Outer Dimensions (inches) | 1x1x1 |

1 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com