

Catalog Number: PIK-12
Product ID: 7TAA263620R0106
UPC Number: 78378685961
Status: Active

Aluminum Insulated Service Entrance Splice - Conductor Range #2 ACSR - #1-#2 Stranded/Compressed (Die CSA-22) to #4 ACSR - #2 Solid/Compressed (Dies 5/8, TU, BG), Body 1.702 inch long x .577 inch diameter. Sleeve 2.719 inch long x .585 inch diameter with End Caps - .740 inch Diameter x .562 inch deep. Color Red/Orange.

North American Specifications (UNSPSC)

UNSPSC	39121409 Wire connectors
IGCC	4543 Wire connectors
Brand Name	Homac
Type	Splice
Size	Body 1.702 inch long x .577 inch diameter. Sleeve 2.719 inch long x .585 inch diameter with End Caps - .740 inch Diameter x .562 inch deep
Connection	Compression/Crimp
Wire Size	#2 ACSR - #1-#2 Stranded/Compressed
Material	Aluminum
Finish	Bare
Insulation	Yes
Environmental Conditions	All Seasons / Conditions

Packaging

Inner Quantity	100
Inner Dimensions (inches)	19.62x4x4.5
Outer Quantity	500
Outer Dimensions (inches)	21.25x5x16.25
Weight Uom	0.04 lbs. Each

Documents / Support Tools

Safety Data Sheet (SDS) Global	SDS-00042-TB2
--------------------------------	---------------

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com