VH221NAWKGL

Safety switch, heavy duty, fused, viewing window, NEMA 12, 240V, 30A, 2 pole, neutral installed, ground lugs



Main

| Product | Single Throw Safety Switch |
|---------------------------|--|
| Duty Rating | Heavy duty |
| Device Application | Heavy application |
| Disconnect Type | Fusible disconnect |
| Factory Installed Neutral | Neutral (factory installed) |
| Number of Poles | 2 |
| Current Rating | 30 A |
| Voltage Rating | 250 V DC 240 V AC |
| Enclosure Rating | NEMA 12 galvannealed steel |
| Motor power hp | 1.5 Hp at 240 V AC 50-60 Hz for 1 phase motors 3 Hp at 240 V AC 50-60 Hz for 3 phase motors 3 Hp at 240 V AC 50-60 Hz for 1 phase motors 7.5 Hp at 240 V AC 50-60 Hz for 3 phase motors 5 hp at 250 V DC |

Complementary

| Short-circuit current | 10 KA for H, K or R without fuse rejection clips |
|-----------------------|--|
| | 200 KA for R with fuse rejection clips |
| | 200 kA for J |
| Fuse type | H or K |
| | R or J |
| Mounting Type | Surface |
| Electrical Connection | Lugs |
| Wiring configuration | 3-wire (2P + N) |
| Wire Size | AWG 12AWG 6 aluminium |
| | AWG 14AWG 6 copper |
| Tightening torque | 45 Lbf.In (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) |
| | 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) |
| | 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10) |
| Depth | 5.195 in (131.95 mm) |
| Width | 6.48 in (164.59 mm) |
| Height | 14.57 in (370.08 mm) |
| Net Weight | 11.02 lb(US) (5 kg) |
| Grounding Kit | Factory installation |
| Service Entrance | Suitable service entrance for USA |
| | Suitable service entrance for Mexico |
| | |

Environment

| 0 115 11 | 10 0 10 50075 | |
|----------------|----------------------|--|
| Certifications | UL listed file E2875 | |

Ordering and shipping details

| Category | 00113-H&HU SW,2&3P,N12,30-200A |
|-------------------|--------------------------------|
| Discount Schedule | DE1 |
| GTIN | 3606485892986 |
| Returnability | No |
| Country of origin | US |
| | |

Packing Units

| PCE |
|----------------------|
| 1 |
| 5.25 in (13.335 cm) |
| 7.50 in (19.05 cm) |
| 16.87 in (42.862 cm) |
| 11.02 lb(US) (5 kg) |
| |

Offer Sustainability

| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
|---------------------------|---|
| EU RoHS Directive | Under investigation |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |