



CE Marked Control Transformer

CE0100E6UCEFS

UPC:786680041075

Dimensions:

Height: XLength: XWidth: X

Notes:Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals, Non-short circuit-proof

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

• Coil Material: Copper windings

• Design: MTE

 Modification 1: Factory-mounted finger-safe terminal shields

 Primary Voltage: 240/416/480/600V, 230/400/460/575V, 220/380/440/550V, 208/500V

 Secondary Voltage: 99/120/130V, 95/115/125V, 91/110/120V, 85/100/110V

• Tap Size: None

• Temperature Rating: 55°C

• Type: CE Marked Control Transformer

• Volt Ampere Rating: 100 VA

Supporting documents:

- Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions
- Eaton Specification Sheet CE0100E6UCEFS



Certifications:

- CSA Certified
- UL Listed
- cUL Certified
- IEC 61558-2

Product compliance:

• RoHS Compliant

© 2016 Eaton. All rights reserved.