VH364NDSGL

Safety switch, heavy duty, fused, viewing window, Type 4X, 600V, 200A, 3 pole, neutral installed, ground lugs



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	Neutral (factory installed)
Number of Poles	3
Current Rating	200 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 4X stainless steel 304
Motor power hp	50 Hp at 480 V AC 50-60 Hz for 3 phase motors 125 Hp at 480 V AC 50-60 Hz for 3 phase motors 60 Hp at 600 V AC 50-60 Hz for 3 phase motors 150 Hp at 600 V AC 50-60 Hz for 3 phase motors 40 Hp at 250 V DC 50 hp at 600 V DC

Complementary

Short-circuit current	10 KA for H, K, J or R without fuse rejection clips
	200 KA for R with fuse rejection clips
	200 kA for J
Fuse type	H or K
	R or J
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	4-wire (3PH + N)
Wire Size	AWG 6250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in² (13.3127 mm²) (AWG 6250 kcmil)
Depth	8.937 in (227.00 mm)
Width	17.474 in (443.84 mm)
Height	28.9 in (734.06 mm)
Net Weight	56.99 lb(US) (25.85 kg)
Grounding Kit	Factory installation
Service Entrance	Suitable service entrance for USA
	Suitable service entrance for Mexico

Environment

Certifications	UL listed file E2875
----------------	----------------------

Ordering and shipping details

00010-H&HU SW,2&3P,N4,SS,30-200A
DE1
3606485894287
No
US

Packing Units

50.165 cm)
25.7175 cm)
80.645 cm)
JS) (25.9 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations