

Han 16HP Direct/B-HSE-M25



Image is for illustration purposes only. Please refer to product description.

Part number	19 39 616 0546
Specification	Han 16HP Direct/B-HSE-M25
HARTING eCatalogue	https://b2b.harting.com/19396160546

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] HP Direct B
Type of hood/housing	Hood

Version

Locking type	Screw locking
Size	16 B
Version	Side entry
Cable entry	1x M25

Technical characteristics

Tightening torque (screw locking)	4 Nm
Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP66 IP68 IP69 / IPX9K acc. to ISO 20653

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
Material (seal)	NBR
Material (locking)	Stainless steel
RoHS	compliant



Pushing Performance

Material properties

ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Specifications	EN 60664-1 IEC 61984
CE	Yes

Commercial data

Packaging size	1
Net weight	338 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors