



Representative

Catalog Number: S203U-K25
UPC Number: 66201917049
EAN Number: 04016779619875
Status: Active
Replacement Catalog: SU203M-K25

Miniature Circuit Breaker, Branch Circuit Protection, Rated Current 25 Amps, 3 Pole, Interrupt Rating 10 kA, Thermal Magnetic Trip Curve K, Voltage up to 240 VAC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, UL 489, CSA 22.2 No. 5

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB, Branch Circuit Protection
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Designed for Allowing Higher In-Rush Current During System Start Up; Example: Motors, Transformers
Standard	UL 489, CSA 22.2 No. 5, IEC 60947-2, UL E212323
Voltage Rating	240 VAC
Amperage Rating	25 Amps
Frequency Rating	50/60 Hertz
Trip Type	K
Interrupt Rating	10 kA
Number Of Poles	3
Auxiliary Contacts	Yes
Length	71 mm
Width	52.5 mm
Height	92 mm
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Inner Quantity	1
Outer Quantity	3
Outer Dimensions (inches)	7x4.25x3.25
Weight Uom	91.5 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com