9001SK43J1RH2

Illuminated selector switch, Harmony 9001SK, plastic, standard handle, red, 30mm, 3 positions, stay put, 110-120V, 2 C/O





Main

Range of Product	Harmony 9001SK	
Product or Component Type	Illuminated selector switch	
Device short name	9001SK	

Complementary

Complementary	
Bezel material	Plastic
Mounting diameter	1.18 in (30 mm)
Operator position information	3 positions
Contacts type and composition	2 C/O
Device presentation	Complete product
Cap/operator or lens colour	Red
[Us] rated supply voltage	110120 V
Light block supply	Via integral transformer
Operator profile	Standard handle
Type of operator	Stay put
Supply frequency	5060 Hz
Size	30 mm
Bulb base	BA 9s
Light source	Incandescent bulb
Cam profile	3

Environment

Protective treatment	TC
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Electrical shock protection class	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13
Product Certifications	CE[RETURN]UL listed file E42259 CCN NKCR[RETURN]CSA LR24590 class 3211 03

Ordering and shipping details

Category	21429-9001 SK,SKY
Discount Schedule	CS1
GTIN	785901941750
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.44 in (11.271 cm)	
Package 1 Width	1.94 in (4.921 cm)	
Package 1 Length	2.25 in (5.715 cm)	
Package 1 Weight	8.11 oz (230 g)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months