

Catalog Number: GAA40BFE4AEFFAXX73
UPC Number: 88861401966
Status: Active

Abbreviated Switchgear, System Type 3 Phase/3 Wire, Bus Type Silver Plated with No Insulation, Main Bus Rating 4000A, Vertical Bus Rating 3,200A, Section Type Feeder, Short Circuit Rating 100kA, System Voltage 480V (508V Maximum), Compartment A Instrument Compartment, Compartment B E3 800A Frame, Compartment C E3 1200A Frame, Compartment D E3 1200A Frame, Enclosure Type Type 1, Door Option No Doors, Connection Options None, Section Depth 72 Inches, Section Width 30 Inches

North American Specifications (UNSPSC)

| | |
|----------------------|---|
| UNSPSC | 39121116 Low voltage switchgear |
| IGCC | 4374 Low voltage switchgear |
| Brand Name | ABB |
| Type | Emax Link |
| Special Features | Barriers between the bus compartment and the cable compartment for increased personnel protection |
| Bus Rating | 4000A |
| Short Circuit Rating | 100kA |
| Size | 92 Inches x 72 Inches x 30 Inches |
| Insulation | No Insulation |
| Enclosure | Type 1 |
| Phase | 3 |

Packaging

| | |
|---------------------------|----------------|
| Outer Quantity | 1 |
| Outer Dimensions (inches) | 72x30x92 |
| Weight Uom | 2134 lbs. Each |

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com