



Representative

Catalog Number: S203M-C0.5
UPC Number: 80432571380
Status: Active

Miniature Circuit Breaker, Supplementary Protector, Rated Current 0.5 Amps, 3 Pole, Interrupt Rating 10 kA, Thermal Magnetic Trip Curve C, Voltage up to 230/400 VAC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, One Delayed Thermal Tripping Mechanism for Overload Protection and an Electromechanic Tripping Mechanism for Short Circuit Protection, UL 1077, CSA 22.2 No. 235

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection
Application	Designed for Protection and Control of the Circuits Against Overloads and Short-Circuits. Residential, Commerical, Industrial
Standard	IEC/EN 60898-1, 60947-2
Voltage Rating	230/400 VAC
Amperage Rating	0.5 Amps
Frequency Rating	50/60 Hertz
Trip Type	C
Interrupt Rating	10 kA
Number Of Poles	3
Auxiliary Contacts	Yes
Length	69 mm
Width	17.5 mm
Height	88 mm
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	0.89 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com