



Powering Business Worldwide

pe.eaton.com

H-Max Drive

HMX07531NAP3L4

UPC:786685571058

Dimensions:

- **Height:** 13.72 IN
- **Length:** 58.51 IN
- **Width:** 14.52 IN

Weight:200 LB

Notes:All boards are varnished. Corrosion resistant. Battery included in all drives for real-time clock. Keypad kit includes HOA bypass. Keypad kit includes HOA, back reset for Europe application. EMI/RFI filters included. DC link choke included.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Brake Chopper:** No brake chopper
- **Options:** Fused drive isolation, Pilot lights
- **Amperage Rating:** 75A
- **Enclosure:** IntelliPass NEMA Type 1
- **Frame Size:** 7
- **Horsepower:** 25 hp
- **Software:** A
- **Voltage Rating:** 208V

Supporting documents:

- [Variable frequency drive - Product overview](#)
- [Eatons Volume 6-Solid-State Motor Control](#)
- [Eaton H-Max HVAC Drives](#)
- [Eaton Specification Sheet - HMX07531NAP3L4](#)

Certifications:

- cUL Certified



- IEC 61800-5-1
- UL 508C
- EN 61800-5-1

Product compliance:

- CE Marked

© 2016 Eaton. All rights reserved.