

CSA Certified StretchStop Lanyards with SofStop Energy Absorber

Description

Miller StretchStop Lanyards combine the integral SofStop® Shock Absorber with a unique stretchable lanyard design to reducing tripping hazards.

Materials

Webbing:

- Safety Strap: Type 7 webbing
- Safety Jacket: Tubular polyester

Thread: Polyester

SofStop Cover: Vinyl

Hardware: Steel

Locking Snap Hooks: 5,000 lb. (22kN)

All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

CSA Approved

Max. Capacity Range: 120-335 lbs. (141 kg)

Maximum Elongation

Distance: 52 in. (in a 6 ft. drop)

Non CSA Approved

Max. Capacity Range: 100-385 lbs. (175 kg)

Maximum Elongation

Distance: 68 in. (in a 6 ft. drop)

Snap Hooks: 5,000 lbs. (22kN)

3/4" (19mm) gate opening

Rebar Hooks: 5,000 lbs. (22kN)

2 1/2 in. (63mm) gate opening

Fall Arrest Force: 1,800 lbs. max.

See table on product for specific weight range and elongation distances.

Certification

Meets all CSA Z259.11-17 requirements.



M2FSFS-TS6C

CSA Certified StretchStop Lanyards with SofStop Energy Absorber

Model Number	Color	Number of Legs	Harness Connection	Anchorage Connection	Lanyard Length
M1ASAR-TS6C	Green	One	Aluminum Snap Hook	Aluminum Rebar Hook	6 ft. (1.8 m)
M1FSFC-TS6C	Green	One	Standard Snap Hook	Large Rebar Hook	6 ft. (1.8 m)
M1FSFR-TS6C	Green	One	Standard Snap Hook	Standard Rebar (2") Hook	6 ft. (1.8 m)
M1FSFS-TS6C	Green	One	Standard Snap Hook	Standard Snap Hook	6 ft. (1.8 m)
M2ASAR-TS6C	Green	Two	Aluminum Snap Hook	Aluminum Rebar Hook	6 ft. (1.8 m)
M2FSFC-TS6C	Green	Two	Standard Snap Hook	Large Rebar Hook	6 ft. (1.8 m)
M2FSFS-TS6C	Green	Two	Standard Snap Hook	Standard Snap Hook	6 ft. (1.8 m)

Available lengths are only from 2.75ft (84cm) – 6 ft (1.8m). Locking Snap Hook – 3/4 in. (19 mm) gate opening; Locking Rebar Hook – 2-1/2 in. (64 mm) gate opening.

Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242
www.millerfallprotection.com

Honeywell Industrial Safety

900 Douglas Pike
Smithfield, RI 02917

USA

Phone: 800.430.5490
Fax: 800.322.1330

Canada

Phone: 888.212.7233
Fax: 888.667.8477



This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.