# 2510FF1P

Manual Starter, fractional horsepower, 16A, 1 pole, 1 HP at 277 VAC, toggle operated, red indicator, NEMA 1 flush mount



#### Main

Product	Single Unit Manual Starter
Туре	F
Overload Relay Type	Melting alloy

Complementary

Complementary		
Current Rating	16 A	
Cable entry	Without	
Horsepower Rating	1 Hp 115 V AC 1 Hp 230 V AC 1 hp 277 V AC	
Voltage Rating	277 V AC	
Number of Poles	1P	
Control Unit	Toggle switch	
Number of Phases	1 phase	
Pilot Light	Red indicator	
Reset	Manual	
Motor starter type	Non reversing	
Electrical Connection	Screw clamp terminals	
Wire Gauge	AWG 14AWG 12 copper	
Height	4.5 in (114.30 mm)	
Width	2.75 in (69.85 mm)	
Depth	2.19 in (55.63 mm)	

#### Environment

Product Certifications	UL listed file E42243 CCN NLRV[RETURN]CSA LR25490 class 3211 05
NEMA Enclosure Rating	Not rated (flush plate) sheet steel standard size

### Ordering and shipping details

Category	21101-2510,2511,2512 F	
Discount Schedule	CP1	
GTIN	785901553816	
Returnability	No	
Country of origin	MX	

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.10 in (7.874 cm)
Package 1 Width	2.60 in (6.604 cm)
Package 1 Length	4.70 in (11.938 cm)
Package 1 Weight	7.68 oz (217.724 g)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration
PVC free	Yes

### Contractual warranty

ontractad warranty	
Warranty	18 months