## Product data sheet Characteristics

# M9LC550

surge arrester cartridge, Multi9 PRD1 75r, 1P, 400 V



Main	
Range of product	Multi9
Product name	Multi9 PRD
Product or Component Type	Cartridge
Poles description	1P

## Complementary

Surge arrester class type	Type 1
Surge arrester technology	MOV
[Ue] rated operational voltage	400 V AC 50-60 Hz
Nominal discharge current	10 kA
Maximum discharge current	75 kA
[Uc] maximum continuous operating voltage	550 V
Maximum [Up] voltage protection level	<1500 V
Local signalling	Mechanical indicator green and red)
Mounting Mode	Plug-in
Mounting Support	Into SPD module
9 mm pitches	2
Height	1.77 in (45 mm)
Width	0.69 in (17.5 mm)
Depth	2.70 in (68.5 mm)
Net Weight	2.89 oz (82 g)
Color	Gray RAL 7035)
Response Time	< 25 ns

#### Environment

LITVITOTITICITE	
Standards	UL 1449
Quality labels	CSA UR
IP degree of protection	NEMA 1
Relative humidity	095 %
Operating altitude	06561.68 ft (02000 m)
Ambient Air Temperature for Operation	-13140 °F (-2560 °C)
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)

#### Ordering and shipping details

Category	08468-SURGE PROTECTION OEM
Discount Schedule	DE1B
GTIN	3606481586124
Returnability	Yes

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.02 in (2.6 cm)
Package 1 Width	3.07 in (7.8 cm)
Package 1 Length	4.25 in (10.8 cm)
Package 1 Weight	3.25 oz (92 g)
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	2.97 lb(US) (1.345 kg)

## Offer Sustainability

<u> </u>	
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	€Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.