

Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 – TS 8880.500

Date : Jan 19, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Baying systems TS 8 – TS 8880.500

created: 19.01.2017 build on www.rittal.com/us-en



Product description

Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear panel: Carbon steel, 1.5 mm Base plates: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting plate and base plates: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
IK code:	IK09
Supply includes:	Enclosure frame Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Roof plate Rear panel Base Plates Mounting plate 4 eyebolts Lock: 3 mm double-bit
Base material:	Carbon steel

Product features

Dimensions:	Height: 1800 mm (71 ") Width: 800 mm (31 ") Depth: 500 mm (20 ")
Mounting plate:	Height: 1696 mm (67 ") Width: 699 mm (28 ")
Number of doors:	2
Packaging unit:	1 pc(s).
Weight/packaging unit:	122.5 kg (270.1 lb.)
EAN:	4028177251076
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180101

Approvals

Approvals:	Bureau Veritas CSA DNV GL Lloyds Register of Shipping Russian Maritime Register of Shipping TÜV UL + C-UL
Certificates:	IK-Code Protection category
Declarations:	Declaration of conformity Manufacturer's declaration