



Main

Product or Component Type	Elbow
Range	I-Line

Complementary

Rated Current	2500 A
Busbar Material	Copper: busbar
Busbar Position	Edgewise
Integral Ground	50 percent capacity integral ground bus
Rated Operational Voltage	600 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
Length	11 in (279.40 mm)
Height	11 in (279.40 mm)

Ordering and shipping details

Category	20041-2500A CU FEEDER BUS IP54 THERMAL
Discount Schedule	PE8
GTIN	785901777199
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	92.12 lb(US) (41.785 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Contractual warranty	
Warranty	18 months