



Series C, F-frame Molded Case Mining Circuit Breaker

E2F050KMA02U62

UPC:782114501177

Dimensions:

Height: 6 INLength: 3.38 INWidth: 4.13 IN

Weight: 4.5 LB

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

Type: Specialty sealedAmperage Rating: 50A

 Interrupt Rating: 65 kAIC at 240V, 25 kAIC at 480V, 18 kAIC at 600V, 10 kAIC at 250 Vdc

• Number Of Poles: Three-pole

• Voltage Rating: 250 Vdc

• Auxiliary Switch: 1A-1B left pigtail rear

• Frame Size: F-frame

• Magnetic Trip Range: 150-500AA

• Maximum Voltage: 600V

• Series: Series C

• Terminals: Line and load

• Trip Type: Non-interchangeable magnetic

• Undervoltage Release: 110-127V right pigtail

rear

Supporting documents:

- E2 Mining Series Sales Brochure
- Eatons Volume 4-Circuit Protection
- Eaton Specification Sheet E2F050KMA02U62



Certifications:

- CSA Certified
- UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.