



### Main

Product or Component Type	Straight length
Range of Product	Powerbus

### Complementary

Line Rated Current	400 A
Busbar Configuration	5A L1 + IG + L2 + N + L3
Busbar Material	Silver plated copper: busbar
Integral Ground	50 percent capacity integral ground bus
Voltage Rating	600 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire (isolated ground and 100 percent neutral)
Length	10 ft (3.05 m)
Enclosure material	Painted aluminium Black
Number of openings	10 each side

### Environment

IP Degree of Protection	IP40
-------------------------	------

### Ordering and shipping details

Category	20171-100A & 225A BUSWAY LENGTHS & FITTINGS
Discount Schedule	PE8
GTIN	3606486278727
Returnability	No

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	90.00 lb(US) (40.823 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>