

MPU22T2F

Unit substation, Mini Power-Zone, plug on,
22kVA, 3 phase, 480V primary, 208Y/120V
secondary, 18kA, C

Main

| | |
|----------------------------|--|
| Product | Sealed Transformer |
| Certifications | UL Listed |
| Type | Mini Power-Zone |
| Enclosure Code | C |
| Insulation Temperature | 365 °F (185 °C) |
| Phase | 3 phase |
| Primary Voltage | 480 V |
| Secondary Voltage | 208Y/120 V |
| Full Capacity Taps | 2 5 % FCBN |
| Power Rating | 22.5 kVA |
| Temperature Rise | 115 °C |
| Winding Material | Copper |
| Interrupt Rating | 18 kA |
| Circuit Breaker Type | Feeder breaker Primary main breaker Secondary main breaker |
| Interior Type | QO Load Center interior |
| Number of Spaces Available | 27 |
| Number of Circuits | 27 |
| Enclosure Type | NEMA 3R hot-rolled steel |

Complementary

| | |
|----------------|---------------------------|
| Height | 45.20 in (1148.08 mm) |
| Width | 27.40 in (695.96 mm) |
| Depth | 13.50 in (342.9 mm) |
| Product Weight | 670.01 lb(US) (303.91 kg) |

Ordering and shipping details

| | |
|-------------------|-----------------------------|
| Category | 16275-MPZ PLUG ON BRANCH CB |
| Discount Schedule | PE2 |
| GTIN | 785901729297 |
| Returnability | No |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 45.20 in (114.8 cm) |
| Package 1 Width | 27.40 in (69.6 cm) |
| Package 1 Length | 13.50 in (34.3 cm) |
| Package 1 Weight | 670.00 lb(US) (303.907 kg) |

Offer Sustainability

| | |
|---------------------------|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| EU RoHS Directive | Under investigation |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|