

CSA Certified Back Biter® Tie Back Lanyards

Description

Miller BackBiter® Tie-Back Lanyards, with a Miller 5K® Snap Hook was designed for tie-back use. The all-in-one lanyard with SofStop® shock absorber and cross-arm anchorage connector reduces inventory and increases worker compliance.

Materials

Webbing: Polyester or Kevlar

SofStop Shock Absorber

- Webbing: Polyester or Kevlar

- Safety Strap

(Inside SofStop): Polyester

Locking Snap

Hook: Steel, ¾ in. (19 mm) gate opening

Miller 5K Locking

Snap Hook: Steel, 3/4 in. (19 mm) gate opening

Thread: Polyester

All hardware meets ASTM (50) fifty-hour salt spray test

requirements.

Technical

CSA Approved

Max. Capacity Range: 120-335 lbs. (141 kg)

Maximum Elongation

Distance: 52 in. (in a 6 ft. drop)

Non CSA Approved

Max. Capacity Range: 100-385 lbs. (175 kg)

Maximum Elongation

Distance: 68 in. (in a 6 ft. drop)
Snap Hooks: 5,000 lbs. (22kN)

3/4" (19mm) gate opening

Rebar Hooks: 5,000 lbs. (22kN)

2 1/2 in. (63mm) gate opening

Fall Arrest Force: 1,800 lbs. max.

See table on product for specific weight range and

elongation distances.



M1FSTB-AS6C

Certification

Meets all CSA Z259.11-17 requirements.

Model Number	Material	Color	Number of Legs	Harness Connection	Anchorage Connection	Lanyard Length
M1FSTB-KS6C	Kevlar webbing	Black	One	Standard Snap Hook	Tie Back Snap Hook	6 ft. (1.8 m)
M1FSTB-AS6C	Tie Back	Green	One	Standard Snap Hook	Tie Back Snap Hook	6 ft. (1.8 m)
M2FSTB-AS6C	Tie Back	Green	Two	Standard Snap Hook	Tie Back Snap Hook	6 ft. (1.8 m)

Locking Snap Hook has a 3/4 in. (19 mm) gate opening. Cordura is a registered trademark of E. I. DuPont. All connectors include 3,600 lb. gate strength.

Limitless Possibilities. Ask the Expert. Technical Service: 800.873.5242

www.millerfallprotection.com

Honeywell Industrial Safety

900 Douglas Pike Smithfield, RI 02917

USA

Phone: 800.430.5490 Fax: 800.322.1330 Canada

Phone: 888.212.7233 Fax: 888.667.8477 This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.