



Actual

Catalog Number: TY200-120-5
Product ID: 7TCG054360R0185
UPC Number: 78621090277
EAN Number: 05414363163930
Status: Active

Cable Tie, Green Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 219.202mm (8.63 Inches), Width of 7.595mm (0.299 Inches), Thickness of 1.905mm (0.075 Inches), Tensile Strength Rating of 540 Newtons (120 Pounds), Bulk Pack

North American Specifications (UNSPSC)

UNSPSC	39121703 Cable ties
IGCC	5034 Cable ties
Brand Name	Catamount
Standard	UL E49405
Width	0.299 in ; 7.595 mm
Length	8.63 in ; 219.202 mm
Thickness	0.075 Inch/1.91mm
Bundle Diameter	2.0 Inches/50.8mm
Material	Nylon/Polyamide 6.6
Color	Green
Lock Mechanism	Plastic Pawl
Tensile Strength	120 Pounds/540 Newtons

European Specifications (ETIM)

ETIM	EC000046 Cable tie
Band width	7.595mm
Length belt/tape/tie	219.202mm
Tie thickness	1.905mm
Min. holding force	540N
Model	Internal toothing
Band closure	Plastic lip/-cam
Material	Plastic
Material quality	Polyamide PA
Surface protection	Untreated
Halogen free	Y
Colour	Green
Transparent	N
Reflective (fluorescent)	N
Text strip	None
Solvable fastener	N
MIL approval	N

Packaging

Inner Quantity	500
Inner Dimensions (inches)	14x14x3
Outer Quantity	2500
Outer Dimensions (inches)	19.7x10.2x9.1
Weight Uom	9.22 lbs. per 1000

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

