



- Grommet Strips protect against damage from sharp panel edges.
- Ideal for tight radii or irregular panel holes and cut-outs.



Unserrated



Serrated

## Heyco® Continuous Grommet Rolls

### Polyethylene 100' (30.5 M) Roll

| FIT PANEL THICKNESS RANGE        |         |         |         | PART NO. |        | DESCRIPTION      | PART DIMENSIONS |     |                  |     |              |     |
|----------------------------------|---------|---------|---------|----------|--------|------------------|-----------------|-----|------------------|-----|--------------|-----|
| Minimum                          | Maximum | Minimum | Maximum | Natural  | Black  |                  | A               |     | B                |     | C            |     |
| in.                              | mm.     | in.     | mm.     |          |        |                  | Overall Height  |     | Bottom Thickness |     | Bottom Width |     |
| in.                              | mm.     | in.     | mm.     |          |        |                  | in.             | mm. | in.              | mm. | in.          | mm. |
| <b>Unserrated</b>                |         |         |         |          |        |                  |                 |     |                  |     |              |     |
| .037                             | 0,9     | .071    | 1,8     | 12391    | 12391B | PGS-071-100'     | .172            | 4,4 | .031             | 0,8 | .109         | 2,8 |
| .072                             | 1,8     | .105    | 2,7     | 12392    | 12392B | PGS-105-100'     |                 |     |                  |     |              |     |
| .106                             | 2,7     | .164    | 4,2     | 12393    | 12393B | PGS-164-100'     | .188            | 4,8 | .047             | 1,2 | .156         | 4,0 |
| <b>Unserrated, with Adhesive</b> |         |         |         |          |        |                  |                 |     |                  |     |              |     |
| .037                             | 0,9     | .071    | 1,8     | 12395    | 12395B | PGSG-071-1-100'  | .160            | 4,1 | .025             | 0,6 | .060         | 1,5 |
|                                  |         |         |         | 12396    | 12396B | PGSG-071-2-100'  | .172            | 4,4 | .031             | 0,8 | .109         | 2,8 |
| .072                             | 1,8     | .105    | 2,7     | 12397    | 12397B | PGSG-105-100'    | .172            | 4,4 | .031             | 0,8 | .109         | 2,8 |
| .106                             | 2,7     | .164    | 4,2     | 12398    | 12398B | PGSG-164-100'    | .188            | 4,8 | .047             | 1,2 | .156         | 4,0 |
| <b>Serrated</b>                  |         |         |         |          |        |                  |                 |     |                  |     |              |     |
| .026                             | 0,7     | .036    | 0,9     | 12399    | 12399B | SPGS-036-100'    | .125            | 3,2 | .031             | 0,8 | .031         | 0,8 |
| .037                             | 0,9     | .071    | 1,8     | 12400    | 12400B | SPGS-071-100'    | .172            | 4,4 | .031             | 0,8 | .109         | 2,8 |
| .072                             | 1,8     | .105    | 2,7     | 12401    | 12401B | SPGS-105-100'    |                 |     |                  |     |              |     |
| .106                             | 2,7     | .164    | 4,2     | 12402    | 12402B | SPGS-164-100'    | .188            | 4,8 | .047             | 1,2 | .156         | 4,0 |
| <b>Serrated, with Adhesive</b>   |         |         |         |          |        |                  |                 |     |                  |     |              |     |
| .037                             | 0,9     | .071    | 1,8     | 12405    | 12405B | SPGSG-071-1-100' | .160            | 4,1 | .025             | 0,6 | .060         | 1,5 |
|                                  |         |         |         | 12406    | 12406B | SPGSG-071-2-100' | .172            | 4,4 | .031             | 0,8 | .109         | 2,8 |
| .072                             | 1,8     | .105    | 2,7     | 12407    | 12407B | SPGSG-105-1-100' | .172            | 4,4 | .031             | 0,8 | .109         | 2,8 |


### Nylon 100' (30.5 M) Roll

| FIT PANEL THICKNESS RANGE        |         |         |         | PART NO. |        | DESCRIPTION    | PART DIMENSIONS |     |                  |     |              |     |
|----------------------------------|---------|---------|---------|----------|--------|----------------|-----------------|-----|------------------|-----|--------------|-----|
| Minimum                          | Maximum | Minimum | Maximum | Natural  | Black  |                | A               |     | B                |     | C            |     |
| in.                              | mm.     | in.     | mm.     |          |        |                | Overall Height  |     | Bottom Thickness |     | Bottom Width |     |
| in.                              | mm.     | in.     | mm.     |          |        |                | in.             | mm. | in.              | mm. | in.          | mm. |
| <b>Unserrated</b>                |         |         |         |          |        |                |                 |     |                  |     |              |     |
| .026                             | 0,7     | .036    | 0,9     | 12411    | 12411B | NGS-036-100'   | .13             | 3,2 | .03              | 0,8 | .03          | 0,8 |
| .037                             | 0,9     | .071    | 1,8     | 12412    | 12412B | NGS-071-100'   | .17             | 4,4 | .03              | 0,8 | .11          | 2,8 |
| <b>Unserrated, with Adhesive</b> |         |         |         |          |        |                |                 |     |                  |     |              |     |
| .037                             | 0,9     | .071    | 1,8     | 12416    | 12416B | NGSG-071-100'  | .17             | 4,4 | .03              | 0,8 | .11          | 2,8 |
| .072                             | 1,8     | .105    | 2,7     | 12417    | 12417B | NGSG-105-100'  |                 |     |                  |     |              |     |
| .106                             | 2,7     | .164    | 4,2     | 12418    | 12418B | NGSG-164-100'  | .19             | 4,8 | .05              | 1,2 | .16          | 4,0 |
| <b>Serrated</b>                  |         |         |         |          |        |                |                 |     |                  |     |              |     |
| .026                             | 0,7     | .036    | 0,9     | 12419    | 12419B | SNGS-036-100'  | .13             | 3,2 | .03              | 0,8 | .01          | 0,8 |
| .037                             | 0,9     | .071    | 1,8     | 12420    | 12420B | SNGS-071-100'  | .17             | 4,4 | .03              | 0,8 | .11          | 2,8 |
| .072                             | 1,8     | .105    | 2,7     | 12421    | 12421B | SNGS-105-100'  |                 |     |                  |     |              |     |
| .106                             | 2,7     | .164    | 4,2     | 12422    | 12422B | SNGS-164-100'  | .19             | 4,8 | .05              | 1,2 | .16          | 4,0 |
| <b>Serrated, with Adhesive</b>   |         |         |         |          |        |                |                 |     |                  |     |              |     |
| .037                             | 0,9     | .071    | 1,8     | 12426    | 12426B | SNGSG-071-100' | .17             | 4,4 | .03              | 0,8 | .11          | 2,8 |
| .072                             | 1,8     | .105    | 2,7     | 12427    | 12427B | SNGSG-105-100' |                 |     |                  |     |              |     |


Standard color natural. Black available by special order only.




UNSERRATED



SERRATED



NO ADHESIVE



ADHESIVE

*Quick Specs*

|                     |                                                                                       |
|---------------------|---------------------------------------------------------------------------------------|
| Material            | Polyethylene or Nylon                                                                 |
| Flammability Rating | 94HB (Nylon only)                                                                     |
| Temperature Range   | -40°F (-40°C) to 149°F (65°C) (Polyethylene)<br>-40°F (-40°C) to 185°F (85°C) (Nylon) |