Product data sheet Characteristics

8903LO80V04

Contactor, Type L, multipole lighting, electrically held, 30A, 8 pole, 600V, 277VAC 60Hz coil, open style





Main	
Product or Component Type	Electrically Held Lighting Contactor
Range of Product	8903L
Control Circuit	Separate control circuit

Complementary

Control Circuit Voltage	277 V AC 60 Hz
Inrush power in VA	180 VA 60 Hz
Hold-in power consumption in VA	35 VA 60 Hz
Current Rating	20 A tungsten 30 A fluorescent
Number of Poles	8P 8 NO
Control Unit	No control units
Pilot Light	No indicator
Electrical Connection	Screw-clamp terminals
Height	5.00 in (127 mm)
Depth	3.11 in (79 mm)
Width	5.63 in (143 mm)

Environment

ZIIVII OIIIII OIII		
Enclosure Type	Not rated (open device)	
Product Certifications	UL Listed[RETURN]CSA	

Ordering and shipping details

Category	21321-8903 L (NOT LX)
Discount Schedule	CP1
GTIN	785901536208
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.50 in (13.97 cm)	
Package 1 Width	7.00 in (17.78 cm)	
Package 1 Length	8.00 in (20.32 cm)	
Package 1 Weight	3.72 lb(US) (1.687 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	

Contractual warranty

14/	
Warranty	18 months
Trainerty	To monate