# YI2A14-020VB3XLEAX



### YI2A14-020VB3XLEAX



#### Ordering information

Туре	Part no.
YI2A14-020VB3XLEAX	2096222

Only suitable for PNP sensors

Other models and accessories -> www.sick.com/



#### Detailed technical data

#### Technical specifications

Accessory groupPlug connectors and cablesAccessory familyConnecting cablesConnection type head AFemale connector, M12, 4-pin, angled, A-codedConnection type head BFlying leadsLocking plug connectorScrew connectionConnector materialTPUConnector colorTransparentLocking nut materialFKMSeal materialFKMWidth across flats13
Connection type head AFemale connector, M12, 4-pin, angled, A-codedConnection type head BFlying leadsLocking plug connectorScrew connectionConnector materialTPUConnector colorTransparentLocking nut materialFixMSeal materialFixMTightening torque0.6 Nm
Connection type head BFlying leadsLocking plug connectorScrew connectionConnector materialTPUConnector colorTransparentLocking nut materialZinc die-cast, nickel-platedSeal materialFKMTightening torque0.6 Nm
Locking plug connectorScrew connectionConnector materialTPUConnector colorTransparentLocking nut materialZinc die-cast, nickel-platedSeal materialFKMTightening torque0.6 Nm
Connector materialTPUConnector colorTransparentLocking nut materialZinc die-cast, nickel-platedSeal materialFKMTightening torque0.6 Nm
Connector colorTransparentLocking nut materialZinc die-cast, nickel-platedSeal materialFKMTightening torque0.6 Nm
Locking nut materialZinc die-cast, nickel-platedSeal materialFKMTightening torque0.6 Nm
Seal material   FKM     Tightening torque   0.6 Nm
Tightening torque 0.6 Nm
Width across flats 13
Cable 2 m, 4-wire, PVC
Jacket material PVC
Jacket color Gray
Cable diameter 5 mm
Conductor cross section 0.34 mm <sup>2</sup>
Shielding Unshielded
Bending radius
Flexible use > 10 x cable diameter
Stationary position > 5 x cable diameter
Display LED 🗸
Nominal voltage, cable 300 V AC
Test voltage, cable   2,000 V AC
Reference voltage
24 V DC
Rated impulse voltage 0.8 kV
Current loading 4 A
Signal type Sensor/actuator cable


Application	Zones with chemicals
Note	Only suitable for PNP sensors
Authorizations	UL
UL File No.	E335179
Enclosure rating	IP65 / IP66K / IP67
Description	LED function display
Specialty	LED function indicator
Ambient operating temperature	
Flexible use	-5 °C +80 °C
Stationary position	-30 °C +80 °C
Head	-25 °C +85 °C
Contamination rating	3
Insulation resistance	100 ΜΩ
Overvoltage category	III
Specific insulation resistance	30 mΩ
Thermal resistance, piping	Flame retardant according to UL 1581 VW1 / CSA FT1

#### Classifications

eCl@ss 5.0	19030312
eCl@ss 5.1.4	19030312
eCl@ss 6.0	27060304
eCl@ss 6.2	27060304
eCl@ss 7.0	27060304
eCl@ss 8.0	27060304
eCl@ss 8.1	27060304
eCl@ss 9.0	27060304
eCl@ss 10.0	27060304
eCl@ss 11.0	27060304
eCl@ss 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

## YI2A14-020VB3XLEAX

Dimensional drawing (Dimensions in mm (inch))



# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

