# NSYS3X3315H

Wall mounted enclosure, Spacial S3X, stainless steel 316L, plain door, 300x300x150mm, IP66





### Main

Range	Spacial
Product name	Spacial S3X
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	11.81 in (300 mm)
Nominal width	11.81 in (300 mm)
Nominal depth	5.91 in (150 mm)
Product installation	Wall-mounting
Device composition	1 body 1 lock door 1 door

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail	
Door type	Solid	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 mm double-bar lock	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Lock zamak Hinge stainless steel Body and door stainless steel 316L	
Surface finish	Body and door Scotch-Brite® brushed Lock chromium plated	
Net Weight	8.90 lb(US) (4.038 kg)	

### Environment

Standards	IEC 62208
Product Certifications	CAN/CSA 22[RETURN]UL 508 type A
IP degree of protection	IP66 IEC 60529
IK degree of protection	IK10 IEC 62262
Environmental characteristic	Corrosive Specific hygiene

### Ordering and shipping details

80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
ES1
3606480155086
No
FR

## Packing Units

0	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.50 in (16.5 cm)
Package 1 Width	12.20 in (31.0 cm)
Package 1 Length	12.40 in (31.5 cm)
Package 1 Weight	8.90 lb(US) (4.038 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	126
Package 2 Height	76.77 in (195.0 cm)
Package 2 Width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)
Package 2 Weight	1150.81 lb(US) (522.0 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------