



Mechanical Cam Switches
BNS 819-D16-L12-100-10
Order Code: BNS00P8

BALLUFF



1) Reference edge, 2) Sealing ring, 3) Cable passage



Display/Operation

Function indicator	1-16. Switch position: None
--------------------	-----------------------------

Electrical connection

Connection type	1-16. Switch position: Screw terminal
-----------------	---------------------------------------

Electrical data

Continuous current	1-16. Switch position: 6 A
Rated operating voltage Ue	1-16. Switch position: 250 V AC
Switching function mechanical	galvanically isolated Dual changeover One NO and one NC
Switching rate	1-16. Switch position: 300/min

Environmental conditions

Ambient temperature	-5...85 °C
IP rating	IP67

Functional safety

B10d (EN ISO 13849-1)	BSE 30.0: 30 mil. Switching operations
-----------------------	--

General data

Approval/Conformity	CE CSA WEEE
Basic standard	IEC 60947-5-1
DIN switch	DIN 43697
Operating principle	1-16. Switch position: Mechanical
Version	Snap contact

Material

Housing material	Aluminum
Housing material, surface protection	Anodized
Material contacts	1-16. Switch position: Silver, gold plated
Plunger material	1-16. Switch position: Stainless steel (1.4034)

Mechanical Cam Switches
BNS 819-D16-L12-100-10
Order Code: BNS00P8

BALLUFF

Mechanical data

Approach direction	longitudinal, parallel to attachment surface
Approach speed	1-16. Switch position: 120 m/min
Distance cam - reference edge	1-16. Switch position: 4.50...5.00 mm
Flange, feed-through	2 threaded exit M25
Installation	Vertical
Life expectancy mechanical	1-16. Switch position: 30 million Switching operations

Number of switching positions	16x Roller bearing
Plunger style	1-16th switch position: Roller bearing
Switch actuation force	1-16. Switch position: 20 N
Switching element	1-16. Switch position: BSE 30.0

Range/Distance

Reproducibility	1-16. Switch position: ± 0.01 mm
-----------------	--------------------------------------

Wiring Diagrams

BSE 30.0

