## Rittal – The System.

Faster – better – everywhere.

## Cable set for OM adapter with springcage terminal – SV 9340.870

Date : Jan 22, 2017



ENCLOSURES

POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

## Cable set for OM adapter with spring-cage terminal – SV 9340.870

created: 22.01.2017 build on www.rittal.com/us-en



## **Product description**

Description:	Pre-assembled connection cables for individual connection of switchgear, top-mounted on OM adaptors with tension spring clamps.
Benefits:	Temperature resistant to 105°C Wire ends with ultrasonic wire-end compression at both ends
Material:	PVC insulation Temperature resistant to 105°C Wire ends with ultrasonic wire-end compression at both ends
Note:	AWG = American Wire Gage
Product features	
Cross-section:	AWG 10 = 5.26 mm <sup>2</sup> $\triangleq$ 6 mm <sup>2</sup>
Dimensions:	Length: 140 mm (5.5 ″) Cross-section: AWG 10 = 5.26 mm <sup>2</sup> $\triangleq$ 6 mm <sup>2</sup>
Packaging unit:	15 pc(s).
Weight/packaging unit:	0.14 kg (0.3 lb.)
EAN:	4028177502727
Customs tariff number:	85444290

© Rittal 2017

ETIM 6.0:	EC000839
ETIM 5.0:	EC000839
eCl@ss 8.0/8.1:	27062302
eCl@ss 7.0/7.1:	27400613
eCl@ss 6.0/6.1:	27400613
eCl@ss 5.1/5.1.4:	27370302
Approvals	
Declarations:	Declaration of conformity
© Rittal Corporation	