QOB220GFI35

Mini circuit breaker, QO, 20A, 2 pole, 120/240VAC, 10kA, 6mA grd fault A, pigtail, bolt on mount, 50 degrees C





Main		
Product	Miniature circuit-breaker	
Range	QO	
Current Rating	20 A	
Voltage Rating	120/240 V AC 120 V AC	
Mounting Type	Bolt-on	

Screw clamp terminal

Circuit Breaker Type Ground fault protecting class A 6 mA
Ratings Not rated

2P

Complementary

Complementary		
Interrupt Rating	10 KA 120/240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz	
Number of Panel Spaces	2	
Wire Size	AWG 14AWG 8 copper AWG 12AWG 8 aluminium	
Tightening Torque	35.40 Lbf.ln (4 N.m) 40.71 lbf.in (4.6 N.m) 0.010.03 in² (420 mm²) (AWG 12AWG 4)	
Height	4.13 in (105 mm)	
Width	1.50 in (38 mm)	
Depth	2.91 in (74 mm)	
Net Weight	0.95 lb(US) (0.431 kg)	

Number of Poles

Electrical Connection

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	122 °F (50 °C)

Ordering and shipping details

Category	00015-QOB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	785901456421
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.20 in (5.588 cm)	
Package 1 Width	3.50 in (8.89 cm)	
Package 1 Length	5.40 in (13.716 cm)	
Package 1 Weight	0.95 lb(US) (0.431 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	

Contractual warranty

Warranty	18 months
----------	-----------