



## Eaton H-Max variable frequency drive

**HMX02734NAP6**

**UPC:**786685569222

### **Dimensions:**

- **Height:** 13.22 IN
- **Length:** 37.3 IN
- **Width:** 9.66 IN

**Weight:**78 LB

**Notes:**All boards are varnished. Corrosion resistant.  
Battery included in all drives for real-time clock.  
Keypad kit includes HOA bypass. Keypad kit includes HOA, back reset for Europe application.  
EMI/RFI filters included. DC link choke included.

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Brake Chopper:** No brake chopper
- **Options:** Third contactor drive isolation
- **Amperage Rating:** 27A
- **Enclosure:** IntelliPass NEMA Type 1
- **Frame Size:** FR5
- **Horsepower:** 20 hp
- **Software:** A
- **Voltage Rating:** 480 V

### **Supporting documents:**

- [Variable frequency drive - Product overview](#)
- [Eaton's Volume 6-Solid-State Motor Control](#)
- [Eaton H-Max HVAC Drives](#)
- [Eaton Specification Sheet - HMX02734NAP6](#)

### **Certifications:**

- IEC 61800-5-1
- EN 61800-5-1
- UL 508C
- cUL Certified

**Product compliance:**

- CE Marked