# QO330PL5392

Mini circuit breaker, QO, 30A, 3 pole, 240VAC, 10kA, Powerlink, plug in mount, 48in leads





# Main Product Circuit breaker Range QO Current Rating 30 A Voltage Rating 240 V AC Mounting Type Plug-in Number of Poles 3P Circuit Breaker Type Standard

HACR rated

Box lugs

$\sim$ -						1 _	
Сc	۱m	n	$\Box$	m	on	па	r٧
$\sim$	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	$\mathbf{v}$			<b>-</b> 11	щ	ıγ

Complementary		
Interrupt Rating	10 kA 240 V AC 50/60 Hz	
Number of Panel Spaces	3	
Provided Equipment	48 in (1219.20 mm) lead	
Wire Size	AWG 12AWG 2 aluminium AWG 14AWG 2 copper	
Tightening Torque	35.40 lbf.in (4 N.m)	
Height	4.57 in (116 mm)	
Width	2.24 in (57 mm)	
Depth	2.91 in (74 mm)	
Net Weight	1.40 lb(US) (0.635 kg)	

Ratings

**Electrical Connection** 

#### Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

#### Ordering and shipping details

Category	09650-POWERLINK QO(B)PL BREAKERS	
Discount Schedule	DE8A	
GTIN	785901956969	
Returnability	Yes	
Country of origin	MX	

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.10 in (10.414 cm)
Package 1 Width	4.30 in (10.922 cm)
Package 1 Length	5.30 in (13.462 cm)
Package 1 Weight	22.40 oz (635.029 g)

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months