

**Catalog Number:** Z2SCUFAK820A0EE04AEX  
**UPC Number:** 88861455309  
**Status:** Active

Emax2, Frame E2.2, Breaking Capacity UL 65kA @ 508V AC, Frame Rating UL 800A, Rating Plug UL 800A, Drawout (Less Cradle), Trip Unit Hi-Touch-LSIG, Measuring Pro and Power Supply 110-240V AC/DC, Communication Module Single MOD-RS-485, Auxiliary Contacts 4 Aux (400V), Closing Coil 110-120V AC/DC, Shunt Trip 110-120V AC/DC, Spring Charge Motor with Standard Aux 100-130V AC/DC, Key Lock in Open Position Different Keys, PLP Padlock

**North American Specifications (UNSPSC)**

|                       |                            |
|-----------------------|----------------------------|
| UNSPSC                | 39121601 Circuit breakers  |
| IGCC                  | 4813 Circuit breakers      |
| Brand Name            | ABB                        |
| Sub Brand             | Emax 2                     |
| Frame                 | E2.2                       |
| Number Of Poles       | 3                          |
| Height                | 13.03 in ; 331 mm          |
| Operating Temperature | 40 Degrees C/104 Degrees F |

**Packaging**

|                           |                      |
|---------------------------|----------------------|
| Outer Quantity            | 1                    |
| Outer Dimensions (inches) | 20.276x20.276x23.622 |
| Weight Uom                | 136.33 lbs. Each     |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)