

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure Stainless steel, disconnect – WM 8018.627

Date : Jan 19, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure Stainless steel, disconnect – WM 8018.627 - WM242608X4

created: 19.01.2017 build on www.rittal.com/us-en



Product description

Material:	Door: Stainless steel, all-round foamed-in PU seal Housing and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Carbon steel, zinc-plated
Surface finish:	Brushed
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Supply includes:	Housing with door Left hand hinge Wall mounting blind-nuts Flange door with universal disconnect cutout

Product features

Dimensions:	Height: 600 mm (24 ") Width: 650 mm (26 ") Depth: 210 mm (8.3 ")
Material thickness::	Housing: 1.5 mm (0.06 ") Door: 2 mm (0.08 ") Mounting plate: 2.5 mm (0.1 ")
Mounting plate:	Height: 570 mm (22 ") Width: 549 mm (22 ")

Packaging unit:	1 pc(s).
Weight/packaging unit:	26 kg (57.3 lb.)
EAN:	83945

2017 © Rittal Corporation