



*Powering Business Worldwide*

[pe.eaton.com](http://pe.eaton.com)



## H-Max Drive

**HMX7D6B4NAP3L3**

**UPC:**786685560816

### Dimensions:

- **Height:** 10.36 IN
- **Length:** 30 IN
- **Width:** 7.88 IN

**Weight:**48 LB

**Notes:**All boards are varnished. Corrosion resistant.  
Battery included in all drives for real-time clock.  
Keypad kit includes HOA bypass. Keypad kit includes HOA, back reset for Europe application.  
EMI/RFI filters included. DC link choke included.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Brake Chopper:** No brake chopper
- **Options:** Fused drive isolation, Pilot lights
- **Amperage Rating:** 7.50A
- **Enclosure:** IntelliDisconnect NEMA Type 12
- **Frame Size:** 4
- **Horsepower:** 2 hp
- **Software:** A
- **Voltage Rating:** 480V

### Supporting documents:

- [Variable frequency drive - Product overview](#)
- [Eaton's Volume 6-Solid-State Motor Control](#)
- [Size B Oversize Type 1, 12 and 3R Enclosure Outline Dims](#)
- [Eaton H-Max HVAC Drives](#)
- [Eaton Specification Sheet -](#)

HMX7D6B4NAP3L3

**Certifications:**

- EN 61800-5-1
- cUL Certified
- UL 508C
- IEC 61800-5-1

**Product compliance:**

- CE Marked

---

© 2016 Eaton. All rights reserved.