

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted enclosures EL, 3-part with punched rails and profile rails, depth-variable – DK 7712.135

Date : Jan 19, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part with punched rails and profile rails, depth-variable – DK 7712.135

created: 19.01.2017 build on www.rittal.com/us-en



Product description

Description: Wall-mounted enclosure with hinged door provides optimum accessibility.

Material: Wall and hinged part: Carbon steel, 1.5 mm
Viewing window: Single-pane safety glass, 3 mm

Surface finish: Powder-coated

Color: Wall and hinged part: RAL 7035
Viewing door: RAL 7035/7015 (slate gray)

**Protection category
IP to IEC 60 529:** IP 55

Supply includes: 4 wall mounting brackets 10 mm
Designer viewing door
1 Mini-comfort handle
1 Security lock 3524 E

Base material: Carbon steel

Product features

Version: with punched rails and profile rails, depth-variable

Dimensions: Height: 612 mm (24 ")
Height units: 12 U (12 U)
Width: 600 mm (24 ")
Depth: 473 mm (19 ")

Depth hinged part:	316 mm (12 ")
Installation depth:	420 mm (17 ")
Clearances:	Clearance height: 549 mm (22 ") Clearance width: 502 mm (20 ")
Wall section:	Depth: 135 mm (5.3 ")
Load capacity:	Hinged part, static (max.): 600 N (600 N)
Packaging unit:	1 pc(s).
Weight/packaging unit:	36 kg (79.4 lb.)
EAN:	4028177324190
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC002500
eCl@ss 8.0/8.1:	27142408
eCl@ss 7.0/7.1:	27180208
eCl@ss 6.0/6.1:	27180208
eCl@ss 5.1/5.1.4:	27180204
Approvals	
Approvals:	UL + C-UL