LHL3640036M

Motor circuit protector, LH, 400A, 3 pole, 600VAC, 25kA, 250VDC, 50kA, lugs, thermal magnetic





Complementary

Terminal identifier	AL400LA
Tightening torque	115.06 Lbf.In (13 N.m) 0.070.47 in² (42 304 mm²) (AWG 1600 kcmil) 115.06 lbf.in (13 N.m) 0.070.20 in² (42127 mm²) (AWG 1250 kcmil)

Ordering and shipping details

eraemig and empping actains		
Category	00935-LAL/LHL BRKR, SW, MAG-GARD	
Discount Schedule	DE2	
GTIN	785901460190	
Returnability	Yes	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.44 in (21.433 cm)	
Package 1 Width	11.13 in (28.258 cm)	
Package 1 Length	17.13 in (43.498 cm)	
Package 1 Weight	16.24 lb(US) (7.365 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Warranty 18 months