

Rittal – The System.

Faster – better – everywhere.

Network/server enclosures TS IT with glazed door, with 482.6 mm (19") mounting angles – DK 5503.120

Date : Jan 19, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Network/server enclosures TS IT with glazed door, with 482.6 mm (19") mounting angles – DK 5503.120

created: 19.01.2017 build on www.rittal.com/us-en



Product description	
Material:	Carbon steel Aluminum Viewing door: Single-pane safety glass, 3 mm
Surface finish:	Enclosure frame: Dipcoat-primed Interior installation: Dipcoat-primed Doors and roof: Dipcoat-primed, powder coated
Color:	Housing frame and panels: RAL 7035 Interior installation: RAL 9005
Supply includes:	Enclosure frame TS 8 with doors and roof plate Glazed aluminum door, front, 180° hinges Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E Two 482.6 mm (19") mounting sections front and rear, variably mounted on support strips with quick-release fasteners Spacers to raise the fan cover plate, for passive cooling (supplied loose) Connection accessories for potential equalization with earthing point (supplied loose) 50 multi-tooth screws M5, captive nuts M5, conductive (supplied loose) IPPC pallet 1 Roof plate, multi-piece, removable, with side cable entry in the depth and covered cut-out for fan mounting plate 1 Carbon steel door at the rear, 180° hinges
Note:	Door opening may vary depending on site requirements or applications.
Base material:	Carbon steel

Product features	
------------------	--

Dimensions:	Height: 1200 mm (47 ") Width: 800 mm (31 ") Depth: 800 mm (31 ")
Installation height for components:	24 U (24 U)
Distance between levels as delivered:	545 mm (21 ")
Load capacity:	19" level: 15000 N (15000 N)
Packaging unit:	1 pc(s).
Weight/packaging unit:	80.8 kg (178.1 lb.)
EAN:	4028177678484
Customs tariff number:	94032080
ETIM 6.0:	EC002499
ETIM 5.0:	EC002499
eCl@ss 8.0/8.1:	27180207
eCl@ss 7.0/7.1:	27180207
eCl@ss 6.0/6.1:	27180207
eCl@ss 5.1/5.1.4:	27180201
Approvals	
Approvals:	UL + C-UL

2017 © Rittal Corporation