

Rittal – The System.

Faster – better – everywhere.

Network/server enclosures TS IT with glazed door, IP 55, with 19" mounting frame – DK 5515.131

Date : Jan 19, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Network/server enclosures TS IT with glazed door, IP 55, with 19" mounting frame – DK 5515.131

created: 19.01.2017 build on www.rittal.com/us-en



Product description

Material:	Carbon steel Aluminum Glazed aluminum door with 3 mm single-pane safety glass
Surface finish:	Enclosure frame: Dipcoat-primed Interior installation: Dipcoat-primed Doors and roof: Dipcoat-primed, powder coated
Color:	Housing frame and panels: RAL 7035 Interior installation: RAL 9005
Protection category IP to IEC 60 529:	IP 55 only in conjunction with baying seal or screw-fastened side panels
Supply includes:	Enclosure frame TS 8 with doors and roof plate Glazed aluminum door, front, 180° hinges Carbon steel door at the rear, 180° hinges Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E Roof plate, one-piece, solid Base tray and base plate, multi-piece, solid Two 482.6 mm (19") mounting frames, front and rear, depth-variable Baying seal and sealing kit for base plates (supplied loose) Connection accessories for potential equalization with earthing point (supplied loose) 50 multi-tooth screws M5, captive nuts M5, conductive (supplied loose) IPPC pallet
Note:	Door opening may vary depending on site requirements or applications. for enclosures with height and depth: 2000 x 1200 mm / 2200 x 1000 mm / 2200 x 1200 mm, the matching side panels are optionally available and are supplied fitted to the enclosure
Base material:	Carbon steel

Product features	
Dimensions:	Height: 2200 mm (87 ") Width: 600 mm (24 ") Depth: 1200 mm (47 ")
Installation height for components:	47 U (47 U)
Distance between levels as delivered:	745 mm (29 ")
Load capacity:	19" level: 10000 N (10000 N)
Packaging unit:	1 pc(s).
EAN:	4028177706286
Customs tariff number:	94032080
ETIM 6.0:	EC002499
ETIM 5.0:	EC002499
eCl@ss 8.0/8.1:	27180207
eCl@ss 7.0/7.1:	27180207
eCl@ss 6.0/6.1:	27180207
eCl@ss 5.1/5.1.4:	27180201
Approvals	
Approvals:	UL + C-UL
Certificates:	Protection category