



Representative

**Catalog Number:** S804S-C80  
**UPC Number:** 80432546238  
**Status:** Active

High Performance Miniature Circuit Breaker with Cage Terminal, Rated Current 80 Amps, 4 Pole, Trip Curve C, Voltage up to 400/690 VAC, Ultimate Short-Circuit Breaking Capacity 50 kA, IEC/EN 60947-2

**North American Specifications (UNSPSC)**

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB with Cage Terminal
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals, Ring Tongue Compatible
Application	Designed for Use with Medium Magnetic Start Up Currents; Example: Lighting, Control Panels
Standard	IEC 60947-2
Voltage Rating	400/690 VAC
Amperage Rating	80 Amps
Frequency Rating	50/60 Hertz
Trip Type	C
Interrupt Rating	50 kA
Number Of Poles	4
Auxiliary Contacts	Yes
Length	88.5 mm
Width	106 mm
Height	95 mm
Operating Temperature	-25 to +60 Degrees Celcius

**Packaging**

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	1 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)