

# Rittal – The System.

Faster – better – everywhere.

## ► Network/server enclosures TS IT With vented door for room climate control, North American version – DK 5504.210

Date : Jan 19, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Network/server enclosures TS IT With vented door for room climate control, North American version – DK 5504.210

created: 19.01.2017 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

**Material:** Carbon steel

**Surface finish:** Enclosure frame: Dipcoat-primed  
Interior installation: Dipcoat-primed  
Doors and roof: Dipcoat-primed, powder coated

**Color:** Enclosure frame and panels: RAL 9005  
Interior installation: RAL 9005

**Supply includes:** Enclosure frame TS 8 with doors and roof plate  
1 Carbon steel door at the front, vented (vented surface area approx. 85% perforated), 180° hinges  
1 Carbon steel door at the rear, vented (vented surface area approx. 85% perforated), 180° hinges  
1 Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E  
1 Roof plate, multi-piece, removable, with side cable entry in the depth and covered cut-out for fan mounting plate  
4 Spacers to raise the fan cover plate, for passive cooling (supplied loose)

**Note:** Door opening may vary depending on site requirements or applications.

**Base material:** Carbon steel

## Product features

**Dimensions:** Height: 1200 mm (47 ")  
Width: 800 mm (31 ")  
Depth: 1000 mm (39 ")

<b>Installation height for components:</b>	24 U (24 U)
<b>Distance between levels as delivered:</b>	745 mm (29 ")
<b>Load capacity:</b>	19" level: 15000 N (15000 N)
<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	77.8 kg (171.5 lb.)
<b>EAN:</b>	4028177678194
<b>Customs tariff number:</b>	94032080
<b>ETIM 6.0:</b>	EC002499
<b>ETIM 5.0:</b>	EC002499
<b>eCl@ss 8.0/8.1:</b>	27180207
<b>eCl@ss 7.0/7.1:</b>	27180207
<b>eCl@ss 6.0/6.1:</b>	27180207
<b>eCl@ss 5.1/5.1.4:</b>	27180201
<b>Approvals</b>	
<b>Approvals:</b>	UL + C-UL