



# YA39L2TC38E10FX

by Burndy  
Catalog ID: YA39L2TC38E10FX

Cu Comp Terminal, 2 Holes W/InspWindow, 600 kcmil 1470/24 (600 kcmil Flex), 3/8" Stud, 1.25" Spacing, Standard Brll

## Product Details

### General

Color Code	Purple
Connector Type	Terminal
Die Index	400
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Material	Copper
Plated	Y
Plating Type	Tin
Trade Name	HYLUG™
Type	Standard Barrel, Tin Plated
UPC	781810539712

### Dimensions

Dimension - B Length inch	1.42 in
Dimension - L Length Overall mm	117 mm
Dimension - Length Overall inch	4.61 in
Dimension - Pad Width inch	1.91 in
Dimension - Strip Length inch	1-1/2
Dimension - Stud Size inch	3/8
Physical Attribute - Tongue Angle	Straight

### Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600
Voltage - Maximum	35000

### Conductor Related

Conductor - Copper Flex I Size	600 kcmil
Conductor - Copper Flex K Size	600 kcmil
Conductor - Copper Flex M Size	600 kcmil
Conductor - Material	Copper

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

**BURNDY Headquarters**  
47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**  
8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)