

Catalog Number: UPC Number: Status:

AF091FX-DM1D 88861423935 Active

Combination Starter AF09, Non-Reversing Three Phase Fusible Disconnect, Enclosure Type NEMA/UL Type 4X (Stainless Steel), Voltage Rating 120VAC, Line Voltage 575-600V, Overload Relay Setting 3.1-4.2, Fuse Clip Rating/Voltage Fuse Type 30A, 600V Class J, with Three Position Selector Switch Hand/Off/Auto

North American Specifications	(UNSPSC)
UNSPSC	39121521 Motor starter controls
IGCC	4736 Non-Reversing Starters With Fusible Discon-
	nects
Brand Name	ABB
Туре	Combination Starter
Special Features	Durable Protective Finish
Voltage Rating	120VAC
Phase	Three
Size	AF09
Enclosure	NEMA/UL Type 4X (Stainless Steel)
Packaging	
Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	1 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com