



### Catalog No. RMS212612HRGR

**Description:** MTR STACK 6-125A 3PH1PH RING SKT 42-100K

**UPC No** 783164684131

**Home > Modular Metering > ReliaMod > ReliaMod Meter Module**

#### Descriptors

Category	ReliaMod Meter Module
----------	-----------------------

#### Specifications

Enclosure	N3R Outdoor
Socket Amperage	125 A
Main Phase Input	3-Phase
Socket Phase Output	1-Phase
Voltage	120/240V
Socket Type	Ring Type
No of Sockets	6
Socket Factory Installed Jaw Configuration	4-Jaw
Socket Bypass	None
Horizontal Bus Amperage	1200 A
Tenant Neutral Lugs (Per each socket) AWG/kcmil Al/Cu	#14-2/0
Tenant Ground Lugs (Per each socket) AWG/kcmil Al/Cu	#14-2/0
Meter Module Tenant Breaker Provisions	Only Accepts 42-100 KAIC TEY/TEYF/TEYL Tenant Breakers
Additional Notes	For tenant breaker load lugs, please refer to breaker specifications
Height (Inches)	72.2
Depth (Inches)	9.5
Width (Inches)	13.9
Estimated Weight (lbs)	175
Meter Mod III to ReliaMod Horizontal Bus Connections	ABB ReliaMod horizontal bus does not match up to GE Meter Mod III horizontal bus, so any ReliaMod section cannot be connected to any GE Meter Mod III section and vice versa without a bus transition adapter section. Please refer to the ReliaMod bus transition adapters in the Buylog for more information.