



Representative Image

Catalog No. 2TLA050013R1432

Description: "MKEY8M, SOL NPT, 24V MET. FLEX KEY"

UPC No 804325834483

Home > Machine Safety > Safety Sensors, Switches, Locks & Gate Boxes

Mechanical Solenoid Safety interlock switch, die cast housing and head, electro-magnetic lock (power to lock), 2000N holding force. 24VDC coil, 2NC(locked)+2NC(actuator inserted). 3x 1/2NPT conduit entries. Delivered with metal flex key.

Descriptors

Category	Safety Sensors, Switches, Locks & Gate Boxes
Type	Process Lock

Specifications

Product Class	Safety Locks & Process Locks
Product Main Type	MKey
Supply Voltage	24VDC
Outputs	Contact
Number of Outputs	3NC + 1NO
Degree of Protection	IP67

Classifications

ETIM 4	EC002593 - Position switch with interlocking
ETIM 5.0	EC002593 - Position switch with interlocking
ETIM 6.0	EC002593 - Position switch with interlocking
ETIM 7	EC002593 - Position switch with guard locking
ETIM 8 (Etim8)	EC002593 - Position switch with guard locking

Dimensions

Product Net Depth / Length	47 mm
Product Net Height	176 mm
Product Net Width	46 mm
Product Net Weight	0.74kg

Safety Information

Performance Level	Up to e
-------------------	---------



