

SKU: CLNB-250-38-1-4

UPC: 0783669674514



Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 250, 2 Holes, 3/8in Bolt Size, 1in Hole Spacing, Long Barrel, No Sight Window, 45° Bent Tang, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Long
Connecting Angle	45°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-62
ILSCOs Die Index Number	I-62
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.688
Barrel Length (mm)	42.8752
Dimension G (IN)	0.414
Dimension G (mm)	10.5156
Height (IN)	2.216
Height BX (IN)	2.0625
Height (mm)	56.2864
Inside Diameter (IN)	0.593
Inside Diameter (mm)	15.0622
Length (IN)	3.663
Length (mm)	93.0402
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Mounting Hole Spacing (IN)	1
Mounting Hole Spacing (mm)	25.4
Outside Diameter (IN)	0.751
Outside Diameter (mm)	19.0754
Strip Length (mm)	44.4627
Tang Length (IN)	1.937
Tang Length (mm)	49.1998
Tang Thickness (IN)	0.157

Tang Thickness (mm)	3.9878
Tang Width (IN)	1.088
Tang Width (mm)	27.6352
Weight (LB)	0.215294022066633
Weight BX (LB)	2.38
Width (IN)	1.088
Width BX (IN)	6.875
Width (mm)	27.6352

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	250 kcmil - 1/0 Str
Flex Conductor Range	4/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366967451

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	Yellow

Voltage

Voltage Rating	35 kV
----------------	-------