

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	25 A
Voltage Rating	120/240 V AC 240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	3P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate

Complementary

Interrupt Rating	65 KA 120/240 V AC 50/60 Hz 65 KA 240 V AC 50/60 Hz 65 kA 120 V AC 50/60 Hz	
Number of Panel Spaces	3	
Wire Size	AWG 14AWG 8 copper or aluminium	
Tightening Torque	40.71 lbf.in (4.6 N.m)	
Height	2.99 in (76 mm)	
Width	2.24 in (57 mm)	
Depth	2.91 in (74 mm)	
Net Weight	0.85 lb(US) (0.386 kg)	
	'	

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00926-QO IND SPECIALTY CB
Discount Schedule	DE2A
GTIN	785901362364
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.40 in (6.096 cm)	
Package 1 Width	3.50 in (8.89 cm)	
Package 1 Length	3.80 in (9.652 cm)	
Package 1 Weight	13.60 oz (385.554 g)	

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	

Contractual warranty

Warranty	18 months