

EDB14050EPD

Mini circuit breaker, E-Frame, 50A, 1 pole, 277 VAC, 25 kA max, bolt on, 30 mA ground fault protection



Main

Range of Product	125 A Frame EDB-EGB-EJB
Product or Component Type	Miniature circuit-breaker
Device short name	EDB
Earth-leakage protection class	Class B
Module type	E-Frame
Trip unit rating	1800 A

Complementary

Line Rated Current	50 A
Maximum operating voltage	277 V AC
AWG gauge	AWG 14...AWG 6 copper AWG 12...AWG 4 aluminium
Breaking capacity	18 KA 277 V AC 18 KA 240 V AC 25 KA 120 V AC 18 kA 120/240 V AC
Circuit breaker application	HID rated HACR rated
Earth-leakage sensitivity	30 mA
Electrical connection	Lugs aluminium
Holding Current	630 A
Local signalling	Trip indicator
Mounting Mode	Bolt-on
Number of poles	1
Number of spaces	2
Number of spaces required	2
Product destination	NF panelboard
Protection Type	Short-circuit Overload
Trip unit technology	Thermal-magnetic
Breaking capacity code	D
Tightening torque	34.52 Lbf.in (3.9 N.m) 0.00...0.01 in ² (2.5...6 mm ²) (AWG 14...AWG 10) 49.56 lbf.in (5.6 N.m) 0.02...0.11 in ² (10...70 mm ²) (AWG 8...AWG 2/0)
Height	6.64 in (168.66 mm)
Width	1.96 in (49.78 mm)
Depth	4.05 in (102.87 mm)
Net Weight	2 lb(US) (0.91 kg)

Environment

Product Certifications	cULus[RETURN]IEC
Ambient Air Temperature for Operation	104 °F (40 °C)

Ordering and shipping details

Category	00946-EDB - EPD BREAKERS
Discount Schedule	DE2
GTIN	785901583622
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.50 in (6.35 cm)
Package 1 Width	7.20 in (18.288 cm)
Package 1 Length	5.50 in (13.97 cm)
Package 1 Weight	33.60 oz (952.544 g)

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------