



Representative

Catalog Number: RG12S36
Product ID: 7TBA133440R0454
UPC Number: 62461601119
Status: Active

Battery Unit, Battery Type: lead-calcium, Voltage DC: 12V, Battery Wattage: 36W, self-powered, Colour: factory white, 120/347VAC, no lamps, Battery Run Time (Minimum): 30 minutes

10-year life expectancy, maintenance-free emergency lighting units. 6, 12 and 24 Volts

- Removable front panel on cabinet provides easy access and allows the unit to be mounted at ceiling height
- Solid-state pulse-type charger, current-limited, temperature compensated, short-circuit proof and reverse-polarity protected
- Unit comes standard with electronic lockout and brownout circuits
- Sealed dust-proof transfer relay, test switch and LED indicator lights
- "Long-life, maintenance-free Lead-Acid battery"

North American Specifications (UNSPSC)

UNSPSC	39111709 Emergency light unit
IGCC	3940 Emergency light unit
Brand Name	Lumacell
Type	Battery Unit
Application	Institutional, Industrial, Commercial, Hospitality
Standard	CSA
Wattage	36W
Voltage Rating	120/347VAC, 12VDC
Battery	Lead-calcium
Battery Runtime	30 minutes
Size	16-1/2 Inches Height x 13-1/4 Inches Width
Material	Cabinet: Steel
Mounting	Wall
Color	Factory white

European Specifications (ETIM)

ETIM	EC001957 Emergency luminaire
Material housing	Steel
Colour housing	White
Battery quality	Lead
Voltage type	AC/DC
Nominal voltage	120-347V
Width	337mm

Packaging

Outer Quantity	1
Weight Uom	11 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

