

Catalog Number: UPC Number: Status:

GAA10BFC4AAEFAXX83 88861403171

Active

Abbreviated Switchgear, System Type 3 Phase/3 Wire, Bus Type Silver Plated with No Insluation, Main Bus Rating 10000A, Vertical Bus Rating 3,200A, Section Type Feeder, Short Circuit Rating 65kA, System Voltage 480V (508V Maximum), Compartment A Instrument Compartment, Compartment B Instrument Compartment, Compartment C E3 800A Frame, Compartment D E3 1200A Frame, Enclosure Type Type 1, Door Option No Doors, Connection Options None, Section Depth 84 Inches, Section Width 30 Inches

North American Specifications (UNSPSC)

39121116 Low voltage switchgear
4374 Low voltage switchgear
ABB
Emax Link
Barriers between the bus compartment and the ca-
ble compartment for increased personnel protection
10000A
65kA
92 Inches x 84 Inches x 30 Inches
No Insulation
Type 1
3
1
84x30x92

Weight Uom

2554 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com