

YG2A14-050S01M2A13



YG2A14-050S01M2A13



Ordering information

Other models and accessories -> www.sick.com/

Туре	Part no.
YG2A14-050S01M2A13	2105153

Illustration may differ



Detailed technical data

Technical specifications

Accessory groupPlug connectors and cablesAccessory familyConnection cablesConnection type head AFemale connector, M12, 4-pin, angledConnector nype head BMale connector, M12, 4-pin, straightConnector materialTPUConnector colorBlackLocking nut materialCin die-cast, nickel-platedTightening torque0.6 NmCableSm, 3-wire, PUR	
Connection type head AFemale connector, M12, 4-pin, angledConnection type head BMale connector, M12, 4-pin, straightConnector materialTPUConnector colorBlackLocking nut materialZinc die-cast, nickel-platedTightening torque0.6 Nm	
Connection type head BMale connector, M12, 4-pin, straightConnector materialTPUConnector colorBlackLocking nut materialZinc die-cast, nickel-platedTightening torque0.6 Nm	
Connector materialTPUConnector colorBlackLocking nut materialZinc die-cast, nickel-platedTightening torque0.6 Nm	
Connector colorBlackLocking nut materialZinc die-cast, nickel-platedTightening torque0.6 Nm	
Locking nut material Zinc die-cast, nickel-plated Tightening torque 0.6 Nm	
Tightening torque 0.6 Nm	
Cable 5 m, 3-wire, PUR	
Jacket material PUR	
Jacket color Black	
Cable diameter 4.1 mm	
Conductor cross section 0.34 mm ²	
Shielding Unshielded	
Bending radius	
Flexible use > 10 x cable diameter	
Stationary position > 5 x cable diameter	
Bending cycles ≤ 5,000,000	
Rated impulse voltage 2.5 kV	
Traversing speed ≤ 3.3 m/s	
Travelling distance 5 m	
Acceleration $\leq 5 \text{ m/s}^2$	
Special feature Drag chain use	
Application Zones with chemicals Zones with oils and lubricants Zones with oils and lubricants	
Authorizations CE UL	
Enclosure rating IP65 / IP66K / IP67	
Another and a second seco	
Ambient operating temperature	
Ambient operating temperature Flexible use -25 °C +80 °C	

Head	-25 °C +85 °C
Classifications	
eCl@ss 5.0	19030312
eCl@ss 5.1.4	19030312
eCl@ss 6.0	27060304
eCl@ss 6.2	27060304
eCl@ss 7.0	27060304
eCl@ss 8.0	27060304
eCl@ss 8.1	27060304
eCl@ss 9.0	27060304
eCl@ss 10.0	27060304
eCl@ss 11.0	27060304
eCl@ss 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

PIN assignment



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

